

Technical Data Sheet

Divinol Syntholight FE 5W20

Product description

Divinol Syntholight FE 5W20 is a modern engine oil of SAE 5W20 class. Due to special additive components and base oils Divinol Syntholight FE 5W20 can be called particularly fuel-efficient and emission reducing. Of course, the product also provides a fast lubrication of the engine and thus significantly reduces wear in the cold-starting period of the motor. Divinol Syntholight FE 5W20 offers an optimum oil supply and therefore lubrication reliability in terms of the oil film.

Advantages:

- unique dispersion properties ensure excellent engine cleanliness
- excellent cleaning properties of all engine components
- corrosion protection
- excellent anti-wear properties
- outstanding reliability of the lubricating film
- very high aging stability

Specification

API SN; ILSAC GF 4/5

Manufacturer performance

Chrysler MS-6395; Ford WSS-M2C-930A/945A/946A; GM 6094 M; GM DEXOS 1

Suitable for all cars of the GM group, where GM DEXOS 1 in SAE class 5W-20 is necessary.

Characteristics

SAE Grade:	5W20
Ash / Sulfate DIN 51575:	0.9 %
Colour / DIN ISO 2049:	2.0
Viscosity/40°C / DIN 51 562:	46 mm ² /s
Viscosity/100°C / DIN 51 562:	8.3 mm ² /s

49370

08/2016-49370-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight FE 5W20

Viscosity index / DIN ISO 2909:	160
Density/15°C / DIN 51 757:	0,85 g/cm ³
Pour point / DIN ISO 3016:	≤ -33 °C
Flash point (Cleveland) / DIN ISO 2592:	≥ 200 °C
TBN:	6 mgKOH/g

Application

Divinol Syntholight FE 5W20 is recommended for Otto / gasoline engines with or without exhaust after treatment systems considering the manufacturers instructions in each case.

49370

08/2016-49370-8

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2