

Technical Data Sheet

Divinol Syntholight HC-FE 5W-30

Product description

Divinol Syntholight HC-FE 5W-30 is a smooth-running engine oil made by use of the most advanced HC synthesis technology. It is based on additives with low ash content (low-saps) for application in the most modern spark-ignition and diesel engines. Due to the HC synthesis technology, Divinol Syntholight HC-FE 5W-30 has a significantly lower evaporation propensity which has a positive effect on oil consumption. The viscosity class 5W-30 guarantees on the one hand a rapid oil circulation of the engine also with low temperatures and on the other hand a sufficiently thick lubricating film with temperatures of up to 160 C°. Also suitable for LPG/CNG motors. According to the manufacturer's instructions!

Specification

API SN/CF; ACEA C3-12

Manufacturer approval

MB-Approval 229.51; MB-Approval 229.52; VW 502.00/505.00/505.01; BMW Longlife-04

Manufacturer performance

GM OPEL DEXOS 2; Ford WSS-M2C-917 A; Fiat 9.55535-S2; PSA B71 2290

Characteristics

SAE Grade:	5W30
Ash / Sulfate DIN 51575:	0.8 %
Colour / DIN ISO 2049:	3
Viscosity/40°C / DIN 51 562:	65 mm ² /s
Viscosity/100°C / DIN 51 562:	11.5 mm ² /s
Viscosity index / DIN ISO 2909:	170
Density/15°C / DIN 51 757:	0,860 g/cm ³

49260

01/2016-49260-16

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

1 / 2

Technical Data Sheet

Divinol Syntholight HC-FE 5W-30

Pour point / DIN ISO 3016:	-37°C
Flash point (Cleveland) / DIN ISO 2592:	220 °C
TBN:	8.5 mgKOH/g

Application

Divinol Syntholight HC-FE 5W-30 meets the high performance and quality level for modern spark-ignition and diesel engines. Particularly, this oil guarantees the extremely long-lasting efficiency of the subsequent exhaust treatment standards EURO 4 and EURO 5.

49260

01/2016-49260-16

The statements made in this publication are according to our present knowledge. They do not absolve the user from own examinations. A legally binding assurance of certain properties or suitability for a specific use can not be derived from our statements. Possibly existing laws and regulations concerning the handling and use of our products have to be observed by the receiver of our products himself.

2 / 2