



ECO-DRIVE LONGLIFE 3 SAE 5W-30

ECO-DRIVE LONGLIFE 3 SAE 5W-30 is a synthetic high-performance low-friction oil for gasoline and diesel engines in passenger cars. The oil is a LOW SAPS product with a reduced sulphur, ash and phosphorus content. Base oils produced with the latest synthesis technology and carefully chosen innovative high-performance additives help to reduce the sulphated ash content and guarantee reliable wear protection and keep the engine clean. Excellent cold start behaviour ensures optimum lubrication safety during the cold start phase. The product provides reliable protection under extreme conditions and high temperatures.

ECO-DRIVE LONGLIFE 3 SAE 5W-30 is the ideal product for all operating conditions. As it reduces the emissions, it helps to protect the environment.

ECO-DRIVE LONGLIFE 3 SAE 5W-30 has been developed for modern passenger car engines with the latest technological features such as exhaust gas aftertreatment from BMW, Mercedes-Benz and VW/Audi.

ECO-DRIVE LONGLIFE 3 SAE 5W-30 extends the service life of exhaust gas aftertreatment systems and maintains their performance.

Specification

ACEA A3/B4, C3

Approved in compliance with / under a different name

VW standard 504 00, 507 00

BMW Longlife-04

Technical data	Unit	Test according	ECO-DRIVE LONGLIFE 3 SAE 5W-30
Density 15°C	kg/m ³	DIN 51 757	849
Flash point COC	°C	DIN ISO 2592	210
Pourpoint	°C	DIN ISO 3016	-4 2
Viscosity 40°C	mm ² /s	DIN 51562-1	69,8
Viscosity 100°C	mm ² /s	DIN 51562-1	11,6
VI		DIN ISO 2909	162

The given data are typical data. Please observe operating instructions.

K10-00000-1431-03/09

DRIVE FIRST CLASS!

PROFI-TECH GmbH * Kimmeltgässle 1-3 * D-73333 Gingen / Fils * Germany

Phone: +(49) 7162 9440-0 * Fax: +(49) 7162 9440-29 * Email: info@profi-tech.com * Internet: www.profi-tech.com

PROFI-CAR is a international registered Trademark of PROFI-TECH GmbH

