



## SYNTH-TECH FS PAO SAE 5W-30

**SYNTH-TECH FS PAO SAE 5W-30** is fully-synthetic high-performance low-friction oil for gasoline and diesel engines in passenger cars with low sulphur-, ash- and phosphorus content (low SAP). Newest group IV base oil technology (PAO) and tuned out absolutely new high-performance additives with low sulphate ash guarantee excellent wear protection and highest engine cleanliness. An excellent cold start behavior ensures optimum lubrication safety in the cold running phase. Extreme load and high temperatures be sure.

**SYNTH-TECH FS PAO SAE 5W-30** can be used under all operating conditions.

**SYNTH-TECH FS PAO SAE 5W-30** was especially developed for diesel engines with particulate filter (DPF's) and is furthermore compatible with catalytic converters of gasoline engines (CAT's).

**SYNTH-TECH FS PAO SAE 5W-30** extends the lifetime of the emission control systems and keeps the functioning upright.

### Specification

ACEA A3/B4/C3

API SN/CF

### Level

MB-Freigabe 229.51

BMW Longlife-04

VW Norm 502 00/ 505 00/ 505 01

FIAT 9.55535-S2

Technical data	Unit	Test according	SYNTH-TECH FS PAO SAE 5W-30
Density at 15°C	kg/m <sup>3</sup>	DIN EN ISO 12185	0,846
Viscosity at 40°C	cSt	DIN 51562-1	61,5
Viscosity at 100°C	cSt	DIN 51562-1	11,5
VI		DIN ISO 2909	180
Flashpoint COC	°C		232
Pourpoint	°C	DIN ISO 3016	-42

The given data are typical data. Please observe operating instructions!

K10 09/12

## DRIVE FIRST CLASS!

PROFI-TECH GmbH \* Kimmeltgässle 1-3 \* D-73333 Gingen / Fils \* Germany

Phone: +(49) 7162 9440-0 \* Fax: +(49) 7162 9440-29 \* Email: info@profi-tech.com \* Internet: www.profi-tech.com

PROFI-CAR is a international registered Trademark of PROFI-TECH GmbH

